



HAL
open science

Impact of changing the wet deposition schemes in Idx on 137-cs atmospheric deposits after the Fukushima accident

Arnaud Quérel, Denis Quélo, Yelva Roustan, Anne Mathieu, Mizuo Kajino, Thomas Sekiyama, Kouji Adachi, Damien Didier, Yasuhito Igarashi, Takashi Maki

► To cite this version:

Arnaud Quérel, Denis Quélo, Yelva Roustan, Anne Mathieu, Mizuo Kajino, et al.. Impact of changing the wet deposition schemes in Idx on 137-cs atmospheric deposits after the Fukushima accident. HARMO 2016 - 17th International Conference on Harmonisation within Atmospheric Dispersion Modelling for Regulatory Purposes, László Bozó, Zita Ferenci, May 2016, Budapest, Hungary. pp.598-602. irsn-04670842

HAL Id: irsn-04670842

<https://irsn.hal.science/irsn-04670842v1>

Submitted on 13 Aug 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Copyright

**17th International Conference on
Harmonisation within Atmospheric Dispersion Modelling for Regulatory Purposes
9-12 May 2016, Budapest, Hungary**

**IMPACT OF CHANGING THE WET DEPOSITION SCHEMES IN LDX ON 137-CS
ATMOSPHERIC DEPOSITS AFTER THE FUKUSHIMA ACCIDENT**

*Arnaud Quérel¹, Denis Quélo¹, Yelva Roustan², Anne Mathieu¹, Mizuo Kajino³, Thomas Sekiyama³,
Kouji Adachi³, Damien Didier¹, Yasuhito Igarashi³, Takashi Maki³*

¹IRSN, PRP-CRI, SESUC, BMCA, Fontenay-aux-Roses, France

²CEREA, ENPC/EDF R&D, Champs-sur-Marne, France

³MRI, Japan Meteorological Agency, Tsukuba, Japan

Abstract: The Fukushima-Daiichi release of radioactivity is a relevant event to study the atmospheric dispersion modelling of radionuclides. Actually, the atmospheric deposition onto the ground may be studied through the map of measured Cs-137 established consecutively to the accident. The limits of detection were low enough to make the measurements possible as far as 250km from the nuclear power plant. This large scale deposition has been modelled with the Eulerian model ldx. However, several weeks of emissions in multiple weather conditions make it a real challenge. Besides, these measurements are accumulated deposition of Cs-137 over the whole period and do not inform of deposition mechanisms involved: in-cloud, below-cloud, dry deposition.

In a previous study (Quérel et al., 2016), a comprehensive sensitivity analysis was performed in order to understand wet deposition mechanisms. It has been shown that the choice of the wet deposition scheme has a strong impact on assessment of deposition patterns. Nevertheless, a “best” scheme could not be highlighted as it depends on the selected criteria: the ranking differs according to the statistical indicators considered (correlation, figure of merit in space and factor 2). A possibility to explain the difficulty to discriminate between several schemes was the uncertainties in the modelling, resulting from the meteorological data for instance. Since the move of the plume is not properly modelled, the deposition processes are applied with an inaccurate activity concentration in the air. In the framework of the SAKURA project, an MRI-IRSN collaboration, new meteorological fields at higher resolution (Sekiyama et al., 2013) were provided and allow to reconsider the previous study.

An update including these new meteorology data is presented. In addition, the focus is put on the deposition schemes commonly used in nuclear emergency context.

Key words: *Fukushima; sensitivity analysis; wet deposition, atmospheric dispersion model*

INTRODUCTION

Wet deposition processes are a crucial component of radionuclide atmospheric transport and soil contamination models. Within atmospheric dispersion model these processes are represented by coefficients that quantify the proportion of scavenged radionuclides per unit of time. Radionuclides are captured by hydrometeors (droplets, snowflakes, etc...) and brought to the Earth's surface by precipitations (rain, snow, etc...). If the capture occurs when the condensed water is aloft in the atmosphere, the phenomenon is called rainout (or in-cloud scavenging). If it occurs during the precipitations, it is called washout (or below-cloud scavenging). These processes are physically separated and can be distinctly represented with their own scavenging coefficients. A wide range of parametrizations are proposed in the scientific literature to determine these coefficients (Duhanyan and Roustan, 2011), and currently no scientific consensus allows to discriminate between them.

Furthermore, the Fukushima case shows significant episodes of wet deposition, making it particularly well suited to study the wet deposition modelling. The release of long-lived species 137-Cs, bound to atmospheric particles, is simulated with the Eulerian long-range dispersion model from the IRSN, ldx (Groëll et al., 2014).

In a previous step, a sensitivity analysis, relying on an ensemble-type approach, was performed in an attempt to discriminate between the various wet deposition schemes proposed in the literature (Quérel et al., 2016). The results of this analysis confirm the strong sensitivity of the simulated deposits to the

choice of deposition schemes, both in terms of magnitude and spatial patterns and similar results were shown in Leadbetter et al. (2015). However it was not possible to identify a particular scheme which lead to an overall improvement in modelling performance and call for caution regarding the results obtained. This could be partly attributed to the uncertainties remaining in the meteorological fields and in the source terms used to drive the atmospheric dispersion model. To go further, finer meteorological data and more up-to-date source terms are now considered. Moreover, since IdX aims at nuclear emergency response, it is suitable to have at our disposal in our modelling framework other parameterizations for wet deposition, like the ones used in similar operational atmospheric dispersion models.

WET DEPOSITION SCHEMES

In addition to the IRSN ones, other wet deposition schemes are considered: those documented in the WMO Task Team report investigating the impact of meteorology on the dispersion of radioactive material from Fukushima-Daiichi Nuclear Power Plant (Draxler et al., 2012). They are issued from the following atmospheric dispersion models: **CMC-MLDP0** (D’Amours et al., 2010), **HYSPLIT** (Draxler and Hess, 1997), **NAME** (Jones et al., 2007), **RATM** (Shimbori et al., 2010) and **FLEXPART** (Stohl et al., 2010). The description of deposition schemes are reported in **Table 1**.

Table 1: Deposition schemes used by models involved in the WMO Task Team.

Atmospheric transport modelling	Below-cloud scheme	In-cloud scheme
CMC-MLDP0	$\Lambda = 0$	$\Lambda = 3 \times 10^{-5}$
FLEXPART	$\Lambda = 10^{-5} I^{0.8}$	Hertel et al. (1995)
HYSPLIT	$\Lambda = 10^{-6}$	Hertel et al. (1995) with $S = 4 \times 10^4$
IRSN	$\Lambda = 5 \times 10^{-5} I$	$\Lambda = 5 \times 10^{-5} I$
NAME	$\Lambda = 8.4 \times 10^{-5} I^{0.79}$	$\Lambda = 3.36 \times 10^{-4} I^{0.79}$
RATM	$\Lambda = 2.78 \times 10^{-5} I^{0.75}$	Hertel et al. (1995) with LWC model

METHODOLOGY AND INPUT DATA

In this study, washout and rainout parameterizations are not considered independently in our ensemble-type approach. Then, model configurations look through a pair of deposition schemes (listed in table1), in addition to meteorological data, precipitation field and source terms. Input data considered are listed below:

- Meteorological data: number 1 and number 8 of Sekiyama’s ensemble (Sekiyama et al., 2013).
- Precipitations: issued from the meteorological simulation or radar rainfall data corrected by rain-gauges observations (Saito et al., 2015).
- Source term: Katata (2015), Saunier (2013) and Terada (2012).

All simulations are performed using the long-range transport model IdX with common settings except for the wet scavenging schemes. Clouds vary between fixed altitudes of 800 m and 5000 m. Dry deposition is modelled through a constant deposition velocity of $2 \times 10^{-3} \text{ m.s}^{-1}$. Horizontal grid comes from the meteorological data whose resolution is 0.03° and vertical resolution follows a non-linear scale ranging from 0 to 5546 m (0, 40, 85, 141, ... 5546 m).

Simulations are compared to a data set of 137-Cs deposit observations which comprises airborne measurements made by the US Department of Energy as well as ground measurements collected by the Ministry of Education, Culture, Sports, Science and Technology of Japan. This data are averaged onto the Model grid (see Figure 1, a).

DATA EXPLOITATION

Three statistical indicators are used to evaluate the performance of simulations to reproduce the deposits:

- Pearson correlation, used to quantify the linear relationship between observations and simulations.
- Factor 2, used to obtain an overall measure of the magnitude of discrepancies between observations and simulations, with equal weighting of low and high values.
- Figure of Merit in Space (FMS), used to compare simulated and observed deposition patterns.

A minimum value of 10kBq.m^{-2} is applied for observed deposits.

Influence of a specific scheme rather than others is investigated within this ensemble type of simulations. Issues considered are: How many simulations are improved by this given choice? Is it a significant improvement? In order to estimate this impact, each simulation performed with the chosen deposition schemes is compared to simulations sharing the same configuration. This comparison is made for each statistical indicator is a distribution of discrepancies for each choice of deposition schemes.

These obtained distributions are then drawn with the help of whisker box.

RESULTS

Figure 1 shows maps of deposits considering different wet deposition schemes. In this example, NAME schemes lead to a greater deposit than IRSN's one.




Figure 1: Deposit (a) Observed; (b) simulated using IRSN deposition schemes; (c) simulated using NAME deposition schemes. Both simulations are performed with Katata source term, Sekiyama n°8 meteorological data and radar rainfall data.

Figure 2 shows an example of the impact on statistical indicators using the possible options for wet deposition. A sensitivity of a given choice is observed on all the indicators. Some wet deposition schemes appear to give better results than others and one can wonder if it is specific to this case study or to the input data (meteorological fields and source terms) included in this ensemble-type approach. These preliminary results need to be consolidated.




Figure 2: Impact of wet deposition schemes on FMS, factor 2 and correlation.

REFERENCES

- Brandt, J., Christensen, J.H., Frohn, L.M., 2002. Modelling transport and deposition of caesium and iodine from the Chernobyl accident using the DREAM model. *Atmospheric Chem. Phys.* 2, 397–417.
- D'Amours, R., Malo, A., Servranckx, R., Bensimon, D., Trudel, S., Gauthier-Bilodeau, J.-P., 2010. Application of the atmospheric Lagrangian particle dispersion model MLDP0 to the 2008 eruptions of Okmok and Kasatochi volcanoes. *J. Geophys. Res.* 115, 1–11. doi:10.1029/2009JD013602
- Draxler, R.R., Arnold, D., Galmarini, S., Hort, M.C., Jones, A.R., Leadbetter, S.J., Malo, A., Maurer, C., Rolph, G., Saito, K., Servranckx, R., Shimbori, T., Solazzo, E., Wotawa, G., 2012. Third meeting of WMO task team on meteorological analyses for Fukushima-Daiichi nuclear power plant accident.
- Draxler, R.R., Hess, G.D., 1997. Description of the HYSPLIT_4 modelling system (Technical Report No. ERL ARL-224). NOAA.
- Duhanyan, N., Roustan, Y., 2011. Below-cloud scavenging by rain of atmospheric gases and particulates. *Atmos. Environ.* 45, 7201–7217. doi:10.1016/j.atmosenv.2011.09.002
- Groëll, J., Quélo, D., Mathieu, A., 2014. Sensitivity analysis of the modelled deposition of Cs-137 on the Japanese land following the Fukushima accident. *Int. J. Environ. Pollut.* 55, 67–76.
- Hertel, O., Christensen, J.H., Runge, E.H., Asman, W.A.H., Berkowicz, R., Hovmand Mads F., 1995. Development and testing of a new variable scale air pollution model - ACDEP. *Atmos. Environ.* 29, 1267–1290. doi:10.1016/1352-2310(95)00067-9
- Jones, A.R., Thomson, D., Hort, M.C., Devenish, B., 2007. The UK Met Office's next-generation atmospheric dispersion model, NAME III, in: *Air Pollution and Its Applications XVII*. Presented at the 27th NATO/CCMS International Technical Meeting on Air Pollution Modelling and its Application, Carlos Borrego, Ann-Lise Norman, Portugal.
- Katata, G., Chino, M., Kobayashi, T., Terada, H., Ota, M., Nagai, H., Kajimo, M., Draxler, R., Hort, M.C., Malo, A., Torii, T., Sanada, Y., 2015. Detailed source term estimation of the atmospheric release for the Fukushima Daiichi Nuclear Power Station accident by coupling simulations of atmospheric dispersion model with improved deposition scheme and oceanic dispersion model. *Atmospheric Chem. Phys.* 15, 1029–1070. doi:10.5194/acp-15-1029-2015
- Leadbetter, S.J., Hort, M.C., Jones, A.R., Webster, H.N., Draxler, R.R., 2015. Sensitivity of the modelled deposition of Caesium-137 from the Fukushima Dai-ichi nuclear power plant to the wet deposition parameterisation in NAME. *J. Environ. Radioact.* 139, 200–211. doi:http://dx.doi.org/10.1016/j.jenvrad.2014.03.018
- Quérel, A., Roustan, Y., Quélo, D., Benoit, J.-P., 2016. Hints to discriminate the choice of wet deposition models applied to an accidental radioactive release. *Int. J. Environ. Pollut.* in press.
- Saito, K., Shimbori, T., Draxler, R., 2015. JMA's regional atmospheric transport model calculations for the WMO technical task team on meteorological analyses for Fukushima Daiichi Nuclear Power Plant accident. *J. Environ. Radioact.* 139, 185–199. doi:10.1016/j.jenvrad.2014.02.007
- Saunier, O., Mathieu, A., Didier, D., Tombette, M., Quélo, D., Winiarek, V., Bocquet, M., 2013. An inverse modelling method to assess the source term of the Fukushima Nuclear Power Plant accident using gamma dose rate observations. *Atmospheric Chem. Phys.* 13, 11403–11421. doi:10.5194/acp-13-11403-2013
- Sekiyama, T., Kajino, M., Kunii, M., 2013. Ensemble simulation of the atmospheric radionuclides discharged by the Fukushima nuclear accident. Presented at the EGU, p. 1695.
- Shimbori, T., Aikawa, Y., Fukui, K., Hashimoto, A., Seino, N., Yamasato, H., 2010. Quantitative tephra fall prediction with the JMA mesoscale tracer transport model for volcanic ash: A case study of the eruption at Asama volcano in 2009. *Pap. Meteorol. Geophys.* 61, 13–29. doi:http://doi.org/10.2467/mripapers.61.13
- Stohl, A., Sodemann, H., Eckhardt, S., Frank, A., Seibert, P., Wotawa, G., 2010. The Lagrangian particle dispersion model FLEXPART version 8.2.
- Terada, H., Katata, G., Chino, M., Nagai, H., 2012. Atmospheric discharge and dispersion of radionuclides during the Fukushima Dai-ichi Nuclear Power Plant accident. Part II: verification of the source term and analysis of regional-scale atmospheric dispersion. *J. Environ. Radioact.* 112, 141–154.